



SIZE	FISHNECK	THREAD (TOP CONNECTION)	MAX. O.D. (BODY)	LENGTH (RUNNING)	OPTIMAL TUBING SIZE	MASS
1 1/2" (1.900)	1.188"	5/8 S.R. (0.938-10UN)	1.516"	APPX. 27 5/8"	1.900"-2.75wt/ft	8.8 lbs.
2 1/16" (2.063)	1.188"	5/8 S.R. (0.938-10UN)	1.657"	APPX. 27 3/4"	2.063"-3.25wt/ft	9 lbs.
2 3/8" (2.375)	1.375"	5/8 S.R. (0.938-10UN)	1.775"	APPX. 27 15/16"	2.375"-4.7wt/ft	12.8 lbs.
2 7/8" (2.875)	1.750"	3/4 S.R. (1.063-10UN)	2.160"	APPX. 30 1/2"	2.875"-6.5wt/ft	19.2 lbs.
3 1/2" (3.500)	1.750"	3/4 S.R. (1.063-10UN)	2.740"	APPX. 30 1/2"	3.500"-9.2wt/ft	23.2 lbs
4 1/2" (4.500)	1.750"	3/4 S.R. (1.063-10UN)	3.776"	APPX. 30 1/2"	4.500"-12.6wt/ft	29 lbs

***NOTE:** DOES NOT PERFORATE P-110 PIPE
MAXIMUM PIPE YEILD STRENGTH IS 80,000 PSI

REV	DATE	DESCRIPTION	BY	TOLERANCES	PART DESCRIPTION	WPC WESTERN PRESSURE CONTROLS LTD. 10021-56 AVENUE EDMONTON, AB. CANADA PHONE: (780) 437-3615 FAX: (780) 437-3616		
				X.X.....±0.015 X.XX.....±0.010 X.XXX.....±0.005 FRAC.....±1/32 ANGLES.....±1/2° BREAK ALL CORNERS 0.030x45°	WESTERN PRESSURE CONTROLS PERFORATOR TECHNICAL CHART			
						MATERIAL:	DWG. NO: H0000CAM00	REV: 0